



Product Specification

Pak-Man



Description

Pak-Man is a medium to heavy-duty grade, reinforced water activated tape. The product is available in natural and white.

Construction

Papers

Top Sheet: 30 lbs/ream Natural or 30 lbs/ream White High Strength Virgin Kraft
Bottom Sheet: 23 lbs/ream MG Natural High Strength Virgin Kraft

Laminant

Non-Asphaltic Polypropylene based polymer laminant
Non-Staining, Flexible, Water Resistant, Complies with FDA; CFR 175.105

Reinforcement

3-Way Fiberglass Reinforcing Pattern
Pattern: Lengthwise threads with diamond cross-machine pattern
Lengthwise Threads: 110 Denier Fiberglass—37/64" spacing (2-1-1-1-2)
Cross-Machine Threads: 150 Denier Fiberglass – Diamond Pattern
less than 1¼" spacing between threads

Adhesive

Smooth, even coating of special high tack, water-activated, modified cornstarch based adhesive

Caliper

6.5 Mills to 8.5 Mills

Performance

Tensile Data*	Machine Direction	Cross Machine Direction
Pak-Man Natural	60-65 lbs/in	25-30 lbs/in
Pak-Man White	60-65 lbs/in	25-30 lbs/in

*Nominal values shown.

Sizes & Put-ups

Pak-Man

Sizes	Rolls/Carton	Cartons/Pallet
2½" x 450'	12	60
3" X 375'	8	84
3" x 450'	10	60
3" x 500'	6	90/105
3" x 500'	10	60
3" x 600'	10	60

Please call our sales service department for custom sizes and put-ups