

PG27

HIGH TEMP PREMIUM GRADE PAPER MASKING TAPE

DESCRIPTION

A high temperature pressure-sensitive masking tape designed for clean removal from a variety of surfaces after exposure to oven temperatures up to 225°F (107°C) for 30 minutes. (Times and temperatures are determined by surface.) Its easy handling, smooth crepe backing exhibits high strength, excellent conformability to irregular surfaces and exceptional cornering. Provides resistance to paint flaking and a clean, well defined paint line.

PRODUCT APPLICATION

Automotive, truck, bus and marine paint masking. Recommend hot to warm removal, although can be removed cold.

GOVERNMENT COMPLIANCE

Meets SAE-AMS-T-21595.

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Fine crepe paper
Adhesive	Natural Rubber/Resin
Adhesion to Steel (oz/in of width)	28 (7.7 N/25mm)
Tensile Strength (lbs/in of width)	26 (114 N/25mm)
Elongation (at break)	10%
Total Thickness (mils)	7.5 (0.19mm)
Quick Stick (oz/in of width)	
To Kraft	8 (2.2 N/25mm)
To Steel	17 (4.6 N/25mm)
Color	Beige



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 09/10

