

PG49

HIGH TEMP PREMIUM PAPER MASKING TAPE

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

DESCRIPTION

A beige, smooth crepe masking tape with pressure-sensitive natural rubber/resin adhesive. Designed for paint masking requiring clean and easy removal from a variety of surfaces. Resists paint flaking and has good quick stick and holding properties. Can be exposed to oven temperatures up to 325°F (163°C) for 30 minutes.

PRODUCT APPLICATION

Automotive, truck, bus and marine paint masking. Recommended hot to warm removal, but can be removed cold.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Smooth Crepe Paper
Adhesive	Natural Rubber/Resin
Adhesion to Steel (oz/in of width)	24 (6.5 N/25mm)
Tensile Strength (lbs/in of width)	24 (105 N/25mm)
Elongation (at break)	11%
Total Thickness (mils)	6.7 (0.17mm)
Quick Stick (oz/in of width)	
To Kraft	5 (1.4 N/25mm)
To Steel	13 (3.5 N/25mm)
Color	Beige



3647 Cortez Road West | Bradenton, FL 34210 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/11

