

# PG16

## HIGH TEMP MEDIUM GRADE PAPER MASKING TAPE

## INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

### DESCRIPTION

A beige, smooth crepe masking tape with a pressure-sensitive natural rubber adhesive. Good quick stick and holding properties. Typical temperature ranges from room temperature to 325°F (160°C) for 20 to 40 minutes.

### PRODUCT APPLICATION

Designed for paint masking requiring adhesion to a variety of surfaces, with clean and easy removal.

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

<b>Backing</b>	Smooth Crepe Paper
<b>Adhesive</b>	Rubber/resin
<b>Adhesion to Steel</b> (oz/in of width) PSTC-1	30 (8.2 N/25mm)
<b>Tensile Strength</b> (lbs/in of width) PSTC-31	25 (109 N/25mm)
<b>Elongation</b> (at break) PSTC-31	8.5%
<b>Total Thickness</b> (mils) PSTC-33	6.7 (0.17mm)
<b>Quick Stick</b> (oz/in of width) PSTC-5	
To Kraft	7 (1.9 N/25mm)
To Steel	14 (3.8 N/25mm)
<b>Color</b>	Beige



3647 Cortez Road West | Bradenton, FL 34210 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/08

