

PG14

HIGH TEMP MEDIUM GRADE PAPER MASKING TAPE

DESCRIPTION

Dark blue coarse crepe paper masking tape with a pressure-sensitive rubber adhesive. Good quick stick and holding properties. This product is designed for paint masking requiring clean and easy removal from a variety of surfaces. Can be exposed to oven temperatures up to 250°F (121°C) for 30 minutes.

PRODUCT APPLICATION

Automotive, truck, bus and marine paint masking. Recommend warm removal, although can be removed cold.

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Coarse Crepe Paper
Adhesive	Rubber/Resin
Adhesion to Steel (oz/in of width)	26 (7.1 N/25mm)
Tensile Strength (lbs/in of width)	23 (100 N/25mm)
Elongation (at break)	7.5%
Total Thickness (mils)	6.7 (0.17mm)
Quick Stick (oz/in of width)	
To Kraft	5 (1.4 N/25mm)
To Steel	12 (3.3 N/25mm)
Color	Dark Blue



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/11

