

# Bloc-It™

## 14 DAY UV RESISTANT EDGE-TREATED SPECIALTY PAPER MASKING TAPE

### DESCRIPTION

Teal colored, high quality fine crepe paper masking tape with a specially formulated pressure-sensitive rubber based adhesive. Designed for exposure to sunlight and special edge treatment that prevents paint bleeding for the crispest, cleanest paint lines possible. Easy, clean removal from most surfaces. Should be used with latex paint. Smooth backing for superior conformability, paint lines and reduced fingertip abrasion. Consistent, easy unwind. Stain and humidity resistant. Secure adhesion.

### PRODUCT APPLICATION

Wherever crisp, clean paint lines are required. Masking can be used on interior surfaces or exposed to weather/out-of-doors conditions up to 14 days.



3647 Cortez Road West | Bradenton, FL 34210 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 3/09

## INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

<b>Backing</b>	Fine Crepe Paper
<b>Adhesive</b>	Synthetic Rubber
<b>Tensile Strength</b> (oz/in of width) MD	23 (100 N/25mm)
<b>Quick Stick</b> (at break)	
To Kraft	4 (1.1 N / 25mm)
To Steel	12 (3.3 N / 25mm)
<b>Elongation</b> (at break)	11%
<b>Adhesion to Steel</b>	26 oz/in (7 N/25 mm)
<b>Total Thickness</b>	5.5 mil (0.14 mm)
<b>Color</b>	Teal

