

## PT-7

### 14 DAY UV RESISTANT SPECIALTY PAINTER'S MASKING TAPE

#### DESCRIPTION

Conformable crepe paper w/ acrylic adhesive. Secure adhesion and clean removal from most surfaces. Resistant to U.V. (up to 14 days), humidity and paint bleed-through.

#### PRODUCT APPLICATION

For interior masking wherever tape (adhesive) will be exposed to sunlight. Compatible w/ polyurethane coated surfaces, wall-paper or new or freshly painted wallboard.

Note: Not recommended for use on lacquer coated surfaces or un-finished wood.



3647 Cortez Road West | Bradenton, FL 34210 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 5/12

## INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

#### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

<b>Backing</b>	Coarse Crepe Paper
<b>Adhesive</b>	Acrylic
<b>Tensile Strength</b> (lbs/in) ASTM D-3759	22 (96 N/25mm)
<b>Elongation</b> (at break) ASTM D-3759	8 %
<b>Adhesion to Steel</b> (oz/in) ASTM D-3330	18 (4.9 N/25mm)
<b>Total Thickness</b> (mil) ASTM D-3652	5.8 (0.147mm)
<b>Temperature Resistance</b>	40°F to 120°F (4°C to 49°C)
<b>Color</b>	Dark Blue

