

TM27

SPECIALTY TRIMFAST MASKING TAPE

DESCRIPTION

Stain resistant temperature resistant paper masking combined with strong PET (polyester) film as insertion lip for painting around window lacings. Lifts moldings away to permit sanding, preparation for easy cornering/curved surfaces. Re-positionable rubber based pressure-sensitive adhesive provides secure hold to and clean removal from both OEM and aftermarket paint systems.

PRODUCT APPLICATION

TrimFast is best suited for bonded / fixed screen rubbers and flush mount / insert moldings on corner and straight moldings around windshield and other automotive glass.

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Color	Natural
Carrier	Crepe Paper/PET Film
Adhesive	Rubber/Resin
Total Thickness (mm)	0.3 (7.6 mils)
Peel Adhesion (N/25mm)	8.2 (30 oz/in.)
Temperature Resistance (1 hour/°C)	107 (225°F)
U.V. Resistance	Limited
Weather Resistance	Limited



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE 08/12

