

PB1

WATER-RESISTANT SPECIALTY PAPER MASKING TAPE

DESCRIPTION

A black, water-resistant medium crepe paper masking tape with a pressure-sensitive natural rubber adhesive. Black color imparts moderate resistance to ultra violet (UV) light.

PRODUCT APPLICATION

Especially suited for bookbinding, packaging, identification, sealing and protection.



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/11

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Medium Crepe Paper
Adhesive	Natural Rubber/Resin
Adhesion to Steel (oz/in of width) PSTC-1	30 (8.2 N/25mm)
Tensile Strength (lbs/in of width) PSTC-31	25 (109N/25mm)
Elongation (at break) PSTC-31	8%
Total Thickness (mils) PSTC-33	5.7 (0.15mm)
Quick Stick (oz/in of width) PSTC-5	13 (3.6N/25mm)
Operating Temp. Range	+50°F ~ +200°F (+10°C ~ +93°C)
Color	Black

