

UG

UTILITY PAPER MASKING TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

Coarse crepe paper masking tape with pressure-sensitive rubber adhesive. Good adhesion and holding properties. Clean, easy removal. Resists wet sanding. Compatible with both water and solvent-based paints. Temperature resistant up to 175°F (80°C) for 30 minutes.

PRODUCT APPLICATION

For paint masking requiring adhesion to and removal from a variety of surfaces.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Crepe Paper
Adhesive	Natural Rubber
Tensile Strength (lbs/in. width) ASTM D-3759	23 (100.7 N/25mm)
Elongation (at break) ASTM D-3759	14%
Adhesion to Steel (oz/in. width) ASTM D-3330	34 (9.3 N/25 mm)
Quick-Stick (oz/in. width) PSTC-5	
To kraft	5 (1.4 N/25mm)
To steel	12 (3.3 N/25mm)
Total Thickness (mils) ASTM D-3652	5.8 (0.15 mm)
Color	Beige



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 09/13

