

# 591

## 7.0 MIL PREMIUM DOUBLE-COATED FLATBACK TAPE

### DESCRIPTION

A bleached flatback paper product coated with a high shear resistant pressure-sensitive natural rubber/resin adhesive on both sides that bond equally as well to almost any surface. White colored easy release treated crepe paper liner allows for either machine or hand application. A recognized standard in the manufacture and repair of golf club grip application.

### PRODUCT APPLICATION

Golf club manufacture and golf grip replacement and repair, photograph mounting, carpet installation, textile manufacturing ("twister room"), steel-rule die (make-ready), and any application that requires two adhesive surfaces for joining.



3647 Cortez Road West | Bradenton, FL 34210 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
[www.itape.com](http://www.itape.com) | [info@itape.com](mailto:info@itape.com)

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/07

## INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

<b>Backing</b>	Bleached flatback
<b>Adhesive</b>	Natural Rubber/Resin
<b>Adhesion to Steel</b> (oz/in of width) PSTC-1	52 (14.2 N/25mm)
<b>Tensile Strength</b> (lbs/in of width) PSTC-31	34 (149 N/25mm)
<b>Elongation</b> (at break) PSTC-31	3%
<b>Total Thickness</b> (mils) PSTC-33 With liner Without liner	12.0 (0.30MM) 7.0 (0.178MM)
<b>Quick Stick to Steel</b> (oz/in of width) PSTC-5	20 (5.5 N/25mm)
<b>Temperature Resistance</b> (Max.)	200°F (93°C)
<b>Color</b>	Beige

