



1626 Bridgewater Road
Bensalem, PA 19020
Toll Free: 800-331-1373
Fax: 215-245-8554
www.prestotape.com

Technical Data Sheet

6175 Medium Tack Film Application Tape

Product Description:

The 6175 is an easy tear, economically priced, embossed high density polyethylene film with medium tack acrylic adhesive specially designed for the clean pick-up and transfer of lettering and graphics. It is wrinkle free and leaves no residue or oil. The 6175 is an all purpose tape for the majority of sign-making applications and is excellent for use with digital and ink jet graphics. It is color coded for easy identification.

Product Properties / Characteristics:

Nominal Results

Thickness:
PSTC 33

6.5
(nominal)

Tack Level:

Medium

Tensile Strength:
PSTC 31 lb/sq in

2000

Elongation (%):
PSTC 31

400

Tear Resistance
(grams)

60

The values listed above are averages determined by standard production testing procedures. The suitability for use shall be determined by the user for the particular application.

Limitations of Warranty: Presto Tape and seller warrants to customers that coated products constructed and delivered by Presto Tape and seller to be free of defects in workmanship and to meet the specifications published by Presto Tape which are available upon request. for a period of six (6) months from date of delivery and in the event of Presto Tape brand product proved to be defective, the excluding solution, at Presto Tape's option, shall be a) refund the purchase price b) repair or c) replace the defective product. No acceptance or responsibility for loss, or expense, implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

This stated Warranty & Limitation of Liability can only be changed through a written agreement by an authorized officer of Presto Tape.