


## Premium 14-Day Blue Masking Tape



- Backing:** Blue Crepe Paper
- Adhesive:** Rubber
- Liner:** N/A
- Colors:** Blue
- Specifications:** N/A
- Standard Sizes:** 24mm x 55M, 36mm x 55M, 48mm x 55M

### Applications

- Painter's grade masking tape for a variety of surfaces
- Interior & exterior uses
- Clean removal masking for metal, glass, wood, vinyl and plastics

### Features

- Crepe Paper Backing
- Rubber Adhesive
- UV Resistant

### Benefits

- Hand Tearable
- Conformable
- Holds up to most paints and other moisture
- Good bond to most surfaces
- Clean removal for up to 14 days
- Suitable for sunlight exposure

### Physical Properties

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	5.3 mils	134.62 mic	ASTM D-1000
<b>Adhesion to Steel</b>	25 oz/in	2.74 N/cm	PSTC-101
<b>Tensile Strength</b>	24 lb/in	42.03 N/cm	ASTM D-1000
<b>Elongation</b>	12%		
<b>Operating Temperature</b>	40 - 130° F	4 - 54° C	

Not recommended for laquer, varnish or urethane finishes. Do not use on wallpaper, unpainted wallboard, wood floors or poorly bonded finishes.

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F

Standard Shelf Life (at 25C): 12 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.