

## Thread Seal Tape



<b>Backing:</b>	PTFE Film
<b>Adhesive:</b>	N/A
<b>Liner:</b>	N/A
<b>Colors:</b>	White
<b>Specifications:</b>	A-A 58092
<b>Standard Sizes:</b>	0.5" x 520", 0.75" x 520", 1" x 520"

### Applications

- Self-lubricating tape for wrapping threads at pipe connections making them easy to assemble and disassemble.
- Extends fatigue life of sealed connections and eliminates system contamination common with messy liquid and paste sealants.

### Features

- PTFE Film

### Benefits

- Self-lubricates
- Easy to use
- Increases ease of assembly
- Unlimited shelf life

### Physical Properties

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	3.5 mils	88.9 mic	ASTM D-1000
<b>Pressure Rating</b>	<10,000 psi		
<b>Temperature Range</b>	-450 - 500° F	-267 - 260° C	

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F  
Standard Shelf Life (at 25C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.