



SPECIFICATIONS

Comfort Flow™/Scrape™ HD Linkable Mats

Product Number 4434 (Comfort Flow with holes)

Product Number 4435 (Comfort Scrape without holes)

Product Number 4436 (Comfort Flow with holes, with grit)

Product Number 4437 (Comfort Scrape without holes, with grit)

Product Size: End-37.125" x 39" Middle-36" x 39"

Rubber Type: Nitrile Rubber (10% recycled content) High Density Closed Cell Foam
Thickness: 1/2"
Color: Black
Durometer: 50 to 55

Testing

- Passes Flammability Standard DOC-FF-1-70
- Static Dissipative
 - Surface to Ground 50% Relative Humidity 3.7×10^8 OHMS
 - Surface to Ground 12% Relative Humidity 4.5×10^8 OHMS
 - Surface to Surface 50% Relative Humidity 9.1×10^8 OHMS
 - Surface to Surface 12% Relative Humidity 9.5×10^8 OHMS
- AATCC Test Method 134-1991 Electrostatic Propensity of Carpets.
Maximum Voltage Negative 0.3 KV.
- UV Stable
- ASTM C1028-96 Static Coefficient of Friction: Dry- .70 Wet- .69
- Anti-microbial treated for lifetime protection against odors and degradation
- Grease and Oil Proof
- Welding safe