

Venom

REINFORCED WATER ACTIVATED TAPE

DESCRIPTION

Natural kraft, 3-Way reinforced, light duty, economy grade, water-activated carton sealing tape, manufactured with a starch based adhesive. VENOM has fiberglass reinforcement in the machine direction and polyester reinforcement in the cross direction.

PRODUCT APPLICATION

Used for two strip sealing cartons top and bottom. Works well on recycled cartons, and non-unitized loads. Recommended for use on light weight to average cartons up to 20 pounds.



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/10/2012

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

CONSTRUCTION (PER 3,000 SQUARE FEET):

Top Ply:	20 Lb. Natural Kraft Paper (virgin fibers)
Bottom Ply:	23 Lb. Natural Kraft Paper (virgin fibers)
Laminating Adhesive:	High Melt Index Polypropylene Base Blend
Remoistenable Adhesive:	14 Lb. Synthetically Modified Starch
MD Reinforcement:	(1-1-1-1) per 70mm (1-1-1-1/1-1-1-1-1) per 72mm 110 Fiberglass
CD Reinforcement:	(1-1-1) Polyester 1.08" spacing, at 44° angle

PHYSICAL PROPERTIES:

Caliper (mils):	5.3
MD Tensile (Lbs./in.):	63
CD Tensile (Lbs./in.):	23

