

## HEAVY DUTY GRADE HOT MELT PET POLYESTER PACKAGING TAPE

### TYPICAL APPLICATIONS

- Extremely tough packaging tape used for heavy duty carton bottom seals
- Ideal for packing military supplies, high value electronic components, as well as sealing hazardous materials and chemicals

### ADVANTAGES AND BENEFITS

- Strongest, thickest packaging tape available
- Excellent high tack adhesion to corrugate and high abrasion resistance
- 2 mil polyester tear resistant film lasts the life of the box

### CONSTRUCTION

Overall Grade/Function: Heavy Duty Grade  
Backing: 50 micron Polyester Film  
Adhesive: Aggressive HP Adhesive

### COLOR(S)

 Clear (CLR)



### STANDARD WIDTH(S)

48 mm      72 mm

### STANDARD LENGTH(S)

50 m      914 m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Thickness	3.4 mils	0.09 mils
Tensile Strength	54 lbs/in width	94.6 N/10 mm
Adhesion to Stainless Steel	95 oz/in width	10.4 N/10 mm
Shear Strength	35,000+ minutes	35,000+ minutes
Elongation	130%	130%
Service Temperature Range	20 F to 150 F	-7 C to 66 C
Application Temperature Range	35 F to 110 F	2 C to 43 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE STANDARDS

ASTM D 1974; ASTM D 5486M-06 Type I, Class 2; ASTM D5486M-06 Type II, Class 2; CID A-A-1684C; FDA Indirect Contact CFR 21, B, 175.105; FDA Indirect Contact CFR 21, 177.1630

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

\*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-HP800- 10/26/2012