

tesa® 4289

Heavy duty tensilised strapping tape

tesa® 4289 is a heavy duty tensilised polypropylene strapping tape with a natural rubber adhesive system.

tesa® 4289 features very high tensile strength with low elongation at the same time. The product is highly abrasion resistant.

Main Application

Bundling of heavy steel pipes, palletising, end tabbing of light gauge rolled steel and finished metals.

Technical Data

▪ Backing material	TPP	▪ Adhesion to steel	5.5 N/cm
▪ Total thickness	150 µm	▪ Elongation at break	50.2 oz/in
	5.9 mils	▪ Tensile strength	35 %
▪ Type of adhesive	natural rubber		375 N/cm
			214.1 lbs/in

Properties

▪ Residue free removal	yes	▪ No discoloration	yes
------------------------	-----	--------------------	-----

For latest information on this product please visit <http://l.tesa.com/?ip=04289>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.