

## tesa® ACX<sup>plus</sup> 7076 High Resistance 60 mil double-sided acrylic foam tape

tesa® ACX<sup>plus</sup> 7076 is a black acrylic foam tape. It consists of a high-performance acrylic system. Due to its unique components, it combines excellent temperature resistance with outstanding cold shock resistance. It is designed for demanding outdoor bonding applications especially in combination with the tesa Adhesion Promoters. The visco-elastic, foamed acrylic core compensates different thermal elongation of bonded parts.

### Main Application

Bonding of panels and reinforcement bars in the following Industries:

- Solar
- Elevator
- Production Equipment
- Transportation

### Technical Data

▪ Backing material	foamed acrylic	▪ Type of adhesive	pure acrylic
▪ Color	deep black	▪ Elongation at break	1000 %
▪ Total thickness	1500 µm 59.1 mils		

### Adhesion to

▪ Steel (initial)	14.0 N/cm 127.9 oz/in	▪ Steel (after 3 days)	35.0 N/cm 319.8 oz/in
▪ Aluminium (initial)	12.0 N/cm 109.6 oz/in	▪ Aluminium (after 3 days)	28.0 N/cm 255.8 oz/in
▪ Glass (initial)	22.0 N/cm 201 oz/in	▪ Glass (after 3 days)	36.0 N/cm 328.9 oz/in

### Properties

▪ Temperature resistance short term	220 °C 428 °F	▪ Resistance to chemicals	● ● ● ●
▪ Temperature resistance long term	120 °C 248 °F	▪ Softener resistance	● ●
▪ Tack	● ●	▪ Static shear resistance at 73,4 °F	● ● ● ●
▪ Ageing resistance (UV)	● ● ● ●	▪ Static shear resistance at 158 °F	● ● ● ●
▪ Humidity resistance	● ● ● ●	▪ T-block	● ● ● ●

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=07076>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

## tesa® ACX<sup>plus</sup> 7076 High Resistance

### 60 mil double-sided acrylic foam tape

#### Additional Information

PV 22 = White PE coated paper liner tesa® ACX<sup>plus</sup> branded  
PV 24 = Blue filmic liner

tesa® ACX<sup>plus</sup> 7076 is recognized according to UL Standard 746C. UL File QQW2.E309290

For latest information on this product please visit <http://l.tesa.com/?ip=07076>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.