

tesa® 4671

Acrylic-coated cloth tape

tesa® 4671 is a strong acrylic-coated cloth tape. It is based on a 120 mesh woven rayon fabric backing and a natural rubber adhesive.

tesa® 4671 is a strong cloth tape for almost every application.

Features:

- high adhesion even on rough surfaces
- excellent tensile strength
- easy to write on
- conformable
- easy, clean removal
- no unpleasant smell
- less reflective surface
- available in 3 colors: black, white, grey

Main Application

- Bundling and reinforcing heavy pipes, profiles etc
- Floor marking
- Fixation of carpets during exhibitions
- Securing sharp edges
- Sealing tins and tubes
- ... and a lot more!

Technical Data

▪ Backing material	acrylic-coated cloth	▪ Elongation at break	9 %
▪ Total thickness	280 µm 11 mils	▪ Tensile strength	70 N/cm 40 lbs/in
▪ Type of adhesive	natural rubber	▪ Temperature resistance (30 min)	140 °C 284 °F
▪ Adhesion to steel	3.5 N/cm 32 oz/in	▪ Mesh	120 count per square inch

Properties

▪ Hand tearability	● ● ● ●	▪ Suitable for die cutting	yes
▪ Straight tear edges	● ● ● ●	▪ Abrasion resistance	● ● ● ●
▪ Easy to write on	yes	▪ Water resistance	● ● ●

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04671>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

tesa® 4671

Acrylic-coated cloth tape

Additional Information

Recommendation: please conduct a test on the application surface before using the product.

For latest information on this product please visit <http://l.tesa.com/?ip=04671>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.