

tesa® 64663

Professional Grade Heavy Duct Tape

tesa® 64663 is a duct tape with an aggressive adhesive for demanding industrial applications such as heavy-duty draping and securing.

tesa® 64663 features a high-grade cloth backing that offers excellent tensile properties while retaining its tearability for easy application. Its high coding weight makes it the ideal candidate for applications on very rough surfaces.

tesa® 64663 offers the perfect tape for professional use in highly demanding industrial, commercial, utility and automotive applications including draping, securing, packaging, bundling, holding, seaming, sealing, protecting, wrapping and repairing.

Main Application

- Sealing of pipes and ducts
- Fastening of construction and protection films
- Application on brickwork and timber
- Sealing of barrels and buckets
- Fixing, closing, packaging, and a lot more!

Technical Data

▪ Backing material	PE laminated cloth	▪ Elongation at break	25 %
▪ Total thickness	304.8 µm 12 mils	▪ Tensile strength	78.93 N/cm 45.1 lbs/in
▪ Type of adhesive	natural rubber	▪ Temperature resistance (30 min)	93 °C 199 °F
▪ Adhesion to steel	7.7 N/cm 70.3 oz/in	▪ Mesh	34 count per square inch

Properties

- | | | | |
|-----------------------|-----|-----------------------|----|
| ▪ Hand tearability | ●●● | ▪ Abrasion resistance | ●● |
| ▪ Straight tear edges | ●●● | ▪ Water resistance | ●● |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=64663>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.