

tesa® 51134

Surface protection and masking tape

tesa® 51134 is a transparent self-adhesive polyethylene tape with an acrylic adhesive, used for masking large areas of plastic parts during professional painting processes.

tesa® 51134 is an interior protection tape for slightly structured surfaces.

tesa® 51134 is suitable for surface protection applications in the appliance industry.

Main Application

- Masking during painting applications
- Protection of various surfaces against dust and damage
- Appliance surface protection
- Temporary automotive surface protection

Technical Data

▪ Backing material	PE film	▪ Elongation at break	200 %
▪ Total thickness	84 µm 3.3 mils	▪ Tensile strength	15 N/cm 8.6 lbs/in
▪ Type of adhesive	acrylic	▪ Temperature resistance	90 °C 194 °F
▪ Adhesion to steel	2.4 N/cm 21.9 oz/in		

Properties

- | | | | |
|------------------------|------|-------------------|-----|
| ▪ Easy to remove | yes | ▪ Flame retardant | ●●● |
| ▪ Paint anchorage | ●●●● | | |
| ▪ Powerwash resistance | ●●● | | |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=51134>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.