

## tesa® 51136

### Surface protection and masking tape

tesa® 51136 is a self-adhesive polyethylene tape with an acrylic adhesive for masking large areas of plastic parts during professional painting processes. The color of the tape provides a good contrast to dark surfaces making for easier and faster positioning.

Furthermore, tesa® 51136 is an interior protection tape for slightly structured surfaces.

tesa® 51136 PV2 is a higher adhesion version for rough surfaces and carpets.

### Main Application

- Masking during painting applications
- Protection of various surfaces against dirt and damage

Temporary surface protection for various vehicle parts

### Technical Data

▪ Backing material	PE film	▪ Elongation at break	300 %
▪ Total thickness	105 µm	▪ Tensile strength	19 N/cm
	4.1 mils		10.8 lbs/in
▪ Type of adhesive	acrylic	▪ Temperature resistance	100 °C
▪ Adhesion to steel	2.4 N/cm		212 °F
	21.9 oz/in		

### Properties

▪ Easy to remove	yes	▪ Scratch resistance	● ● ● ●
▪ Paint anchorage	● ● ● ●	▪ Flame retardant	● ● ● ●
▪ Powerwash resistance	● ● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=51136>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.