

## tesa® 53319

### Moderate Tensile Filament Reinforced Tape

Medium tensile, fiberglass reinforced tape with an aggressive high-tack synthetic rubber resin adhesive. This product has high tear resistance and low elongation. Available Colors: Transparent

### Main Application

- Strapping, bundling, and palletizing
- General-purpose packaging and carton sealing
- "L" and "C" clipping

### Technical Data

▪ Backing material	glassfiber & BOPP	▪ Adhesion to steel	7.7 N/cm
▪ Total thickness	111.76 µm		70.3 oz/in
	4.4 mils	▪ Elongation at break	4.5 %
▪ Type of adhesive	synthetic rubber	▪ Tensile strength	271 N/cm
			154.7 lbs/in

For latest information on this product please visit <http://l.tesa.com/?ip=53319>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.