



### Product Description

**Vibac™ 600 / 6000 Clear, 601 / 6001 Tan, 602 / 6002 White** is a natural rubber and resin adhesive based High Performance Strength Carton Sealing Tape which primary uses are for carton sealing, splicing, bundling and other packaging applications. This product has a conformable film backing coupled with a heavy duty adhesive for demanding packaging applications, heavy cartons and cold temperature applications. **The Vibac™ 600 Clear / 601 Tan / 602 White are suitable for usage with hand held dispensers. Vibac™ 6000 Clear / 6001 Tan / 6002 White are suited for use on semi-automatic and automatic carton sealers.**

### Performance Features

- ▶ Formulated and designed for application at cold temperatures or at room temperature and then stored in an low temperature environment
- ▶ Specifically suited where a high quality adhesive combined with a strong backing is required for those demanding applications.
- ▶ High quality adhesive to seal heavy or recycled cartons.
- ▶ Works well in cold and dusty environments
- ▶ Resists temperature variations
- ▶ Specially Designed release for high speed automated application systems
- ▶ Adheres instantly to recycled corrugated, paper, plastic films and a number of surfaces.
- ▶ Good edge tear and split resistance.
- ▶ High Adhesive properties provide excellent adhesion for difficult applications and recycled fiberboard.
- ▶ Reliable closures.
- ▶ Complies with environmental considerations of ASTM D 1974-92
- ▶ Acceptable by USDA for use on packaging material that have minimal contact and are used and prepared under federal inspection.
- ▶ Meets CID A-A 1684C.
- ▶ ROHS Compliant.
- ▶ Roll to roll consistency increases productivity for improved unit costs.

### Recommended Storage Conditions

Store in original packaging in a clean dry place away from direct sunlight. Temperature of 40°F - 80°F (4°C - 26°C) and relative humidity of 40 to 50% is recommended.

Physical Properties	Standard	Metric	ASTM test Method
Thickness - Backing (BOPP)	1.37 mils	0.035 mm	D3652
Adhesive Thickness	0.79 mils	0.020 mm	D3652
Thickness - Total	2.16 mils	0.055mm	D3652
Adhesion to Steel	32 oz/in width	35 N/100 mm width	D3330
Elongation at Break	180%	180%	D3759
Tensile Strength (longitudinal direction)	22 lbs/in width	394 N/100 mm width	D3759
Shear at 23°C, (1 in.)	120+ minutes	120+ minutes	D3654
Application Temperature - Minimum	32°F	0°C	N/A
Application Temperature Maximum	122°F	50°C	N/A
Adhesive Type	Natural Rubber and Resin Based		
Available Colors	Clear / Tan / White		
Standard Widths	48mm, 72mm		
Standard Lengths - Hand Rolls	50m, 100m		
Standard Lengths - Machine Rolls	914m		



### North America

12 250 boul. Industriel  
Montreal, Quebec, Canada H1B 5M5  
Tel.: 514 640-0250  
Fax: 514 640-6702  
e-mail: sales@vibac.com  
www.vibacgroup.com

The above properties and results obtained refer to the average values of laboratory testing carried out on the sample VIBAC® product. VIBAC® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. VIBAC® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. VIBAC® assumes no responsibility for any damage or injury sustained as a result of the use of its products.



## VIBAC™ 600-6000 CLEAR / 601-6001 TAN / 602-6002 WHITE

Carton Sealing Tape for Hand Dispensers and for  
Semi-Automatic and Automatic Carton Sealers

### Permissible Variations, Standards and Tolerances:

Except in the particulars specified by buyer and expressly agreed to in writing by VIBAC® CANADA INC., all goods or material shall be produced in accordance with VIBAC®'s standard practices. All goods or material, including that produced to meet an exact specification, shall be subject to tolerances and variations consistent with usages of the trade and regular manufacturing practices concerning: dimension, weight, straightness, section, composition and mechanical properties; normal variations in surface, internal conditions and quality; deviations from tolerances and variations consistent with practical testing and inspection methods; and regular manufacturing practices concerning over and under shipments. All "In - Stock" orders are subject to a ten percent (10%) over ship / under ship quantity and all "Non - Stock / Non - Standard" orders are subject to a fifteen percent (15%) over run / under run quantity.

### Warranty and Limited Remedy:

Unless stated otherwise, Vibac warrants that each product meets the applicable specifications at the time Vibac manufactures the product. VIBAC MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the Vibac product is fit for a particular purpose and suitable for user's application especially when used in combination with other products. If the Vibac product is defective within the warranty period, your exclusive remedy and Vibac's and seller's sole obligation will be, at Vibac's option, to replace the product or refund the purchase price. All of Vibac products are limited to a warranty period of six (6) months from date of purchase.

### Limitation of Liability:

Except where prohibited by law, VIBAC® and seller will not be liable for any loss or damage arising from the VIBAC® product, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

VIBAC® reserves the right to make changes without notice or obligation on our products and in the information published about them. The suggestions and information presented herein are based on our research and experience, and believed to be reliable, but accuracy or completeness is not guaranteed. They are only for guidance and are not warranties or binding descriptions. The advice of seller's technical staff is available to the trade, but seller, not controlling or supervising the subsequent manufacture, fabrication, or installation of its products or their use after sale, does not warrant or guarantee such advice.

Since VIBAC® has no control over the conditions under which our product is transported, stored, handled, used or applied, each buyer and user must determine by its own preliminary tests or otherwise whether a product is suitable for its purpose. **THE WARRANTY DESCRIBED SHALL BE IN LIEU OF ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE. NO ONE IS AUTHORIZED BY VIBAC® TO MAKE ORAL WARRANTIES.**

To request additional product information or to arrange for sales assistance, please call, toll free, 1-800-557-0192 or email your request to [sales@vibac.com](mailto:sales@vibac.com)



This product is manufactured by a certified C-TPAT member under a quality system registered to  
ISO 9001 : 2000 and ISO 14001 : 2004 standards