

530

KRAFT UTILITY PAPER FLATBACK TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

An aggressive pressure sensitive flatback with an adhesive that has been specifically designed to offer a strong secure seal on a variety of substrates. 530 performs well under a wide range of temperatures and humidity conditions. This product is not repulpable.

PRODUCT APPLICATIONS

Carton sealing, packaging, silk screening, picture framing, beaming/leasing, splicing, and tabbing

GOVERNMENT COMPLIANCE

PPP-T-42C, Type II
C.I.D. A-A-883B, Type II
Complies with Postal Regulation for Uninsured Packages.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

| | |
|---|---|
| Backing | Kraft Flatback |
| Adhesive | Solvent Cast Natural / Synthetic Rubber |
| Adhesion to Steel (oz/in of width) PSTC-101 | 58 (15.9 N/25mm) |
| Tensile Strength (lbs/in of width) PSTC-131 | 40 (175 N/25mm) |
| Elongation (% at break) | 7 |
| Total Thickness (mils) PSTC-133 | 7.3 (0.18mm) |
| Operating Temperature Range | +40°F ~ +175°F (4.4°C ~ +79°C) |
| Color | Brown |



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/16

