

# CHR<sup>®</sup> 2302

## UHMW Pressure Sensitive Adhesive Tape

**CHR 2302** is manufactured from UHMW (Ultra High Molecular Weight) polyolefin film coated with acrylic adhesive.

### Features/Benefits

**CHR 2302** exhibits excellent abrasion resistance and a low coefficient of friction, making it an excellent protection for surfaces or bearings that experience heavy wear. It is more economical than PTFE tapes. The high-temperature, high-tack acrylic adhesive adheres readily to most dry, clean surfaces, firmly anchoring the product in place.

### Availability

Factory stock for 2302 is in master log form 33 m x 889 mm (36 yd x 35 in). Rolls can be slit in widths ranging from 6.35 mm to 889 mm (0.25 in to 35 in). The product is supplied with a blue poly-film inter-liner, which protects the adhesive, facilitates die cutting, and peels off easily. Brown paper is also available as a custom product.

### Applications

**CHR 2302** can be used to provide an abrasion-resistant, anti-stick, anti-friction surface at temperatures up to 107°C (225 °F). It is frequently used to line chutes and conveyors. The product is often applied to guide rails to reduce noise levels in glass bottling plants. This tape is also used to replace desk drawer bearings, and to provide silky smooth, friction free drawer movement.



## CHR 2302 Properties

Performance tests are run using standard test procedures.

The values presented are typical values and should not be used for specification purposes.

Product Number	2302-3R	2302-5R	2302-10R	2302-20R
Backing Material	Film-UHMW	Film-UHMW	Film-UHMW	Film-UHMW
Adhesive Type	Acrylic	Acrylic	Acrylic	Acrylic
Total Thickness mm (mil)	0.114 (4.5)	0.165 (6.5)	0.292 (11.5)	0.546 (21.5)
Backing Thickness mm (mil)	0.076 (3.0)	0.127 (5.0)	0.254 (10.0)	0.508 (20.0)
Adhesive Thickness mm (mil)	0.038 (1.5)	0.038 (1.5)	0.038 (1.5)	0.038 (1.5)
Adhesion to Steel N/cm (oz/in)	3.8 (35)	4.9 (45)	5.5 (50)	5.5 (50)
Tensile Strength N/cm (lb/in)	35 (20)	70 (40)	140 (80)	254 (145)
Elongation (% at break)	300	350	425	500
Operating Temperature °C (°F)	-40 to +107 (-40 to +225)	-40 to +107 (-40 to +225)	-40 to +107 (-40 to +225)	-40 to +107 (-40 to +225)
Colour	Natural	Natural	Natural	Natural



### Performance Plastics - Tape Solutions

North America | South America | Europe | Asia

For a full list of locations, please visit  
[tapesolutions.saint-gobain.com/contact-us](https://tapesolutions.saint-gobain.com/contact-us)

**IMPORTANT:** It is the user's responsibility to ensure the suitability and safety of Saint-Gobain Performance Plastics products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain Performance Plastics assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

**WARRANTY:** For a period of 6 months, Saint-Gobain Performance Plastics warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1155 | © Saint-Gobain March 2018 | **CHR** and **CHRTape** are trademarks of Saint-Gobain.