



700 • 701 • 702

TECHNICAL DATA

PVC (Polyvinyl Chloride) Carton Sealing Tape for Hand Held Dispensers

Product Description

- ▶ **Vibac™ 700 Clear / 701 Tan / 702 White** are made from a natural rubber and resin based adhesive combined with a PVC (Polyvinyl Chloride) film backing. This pressure sensitive tape provides instant adhesion, possesses excellent quick stick properties and sticks to a wide variety of irregularly shaped surfaces. The natural rubber and resin adhesive has been specifically formulated to provide good instant adhesion to fiberboard, plastic, glass, metallic, printed and painted surfaces. Typical applications would include; carton closure in cold temperature environments, recycled cartons, color coding, strapping, bundling, unitizing, packaging, palletizing, etc. Vibac™ PVC is surface printable. **Vibac™ 700 Clear / 701 Tan / 702 White** are suitable for usage with hand held dispensers.

Performance Features

- ▶ Formulated for applications where temperatures are a factor.
- ▶ Works well in cold and dusty environments.
- ▶ Resistant to moisture and humidity.
- ▶ Adheres instantly to recycled corrugated, paper, plastic films and a number of surfaces.
- ▶ Quick unwind and easily tearable by hand.
- ▶ Good handling characteristics saves time due to ease of dispensing and application.
- ▶ Pressure sensitive tape is surface printable.

Recommended Storage Conditions

- ▶ Store in original packaging in a cool, clean dry place away from direct sunlight. Temperature of 40 -80°F (4-26°C) and relative humidity of 40 to 50% is recommended. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.



Physical Properties	Standard	Metric	ASTM test Method
Adhesive	Natural Rubber and Resins		
Backing	PVC (Polyvinyl Chloride) Film		
Backing Color	Clear, Tan, White		
Backing Thickness	1.3 mils	0.033 mm	D3652
Total Thickness	2.1 mils	0.053 mm	D3652
Adhesion to Steel	18oz/in width	20 N/100 mm width	D3330
Tensile Strength	25 lbs/in width	447 N/100 mm width	D3759
Service Temperature - Minimum	20°F	-7°C	N/A
Service Temperature - Maximum	140°F	60°C	N/A
Elongation at Break	80%		D3759
Available Widths*	48mm, 72mm		
Available Lengths*	50m, 66m, 100m		

* Other dimensions available upon request
Minimum order quantities may apply



North America

12 250 boul. Industriel
Montreal, Quebec, Canada H1B 5M5
Tel.: 514 640-0250
Fax: 514 640-6702
e-mail: sales@vibac.com
www.vibacgroup.com

The above properties and results obtained refer to the average values of laboratory testing carried out on the sample VIBAC® product. VIBAC® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. VIBAC® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. VIBAC® assumes no responsibility for any damage or injury sustained as a result of the use of its products.



VIBAC™ 700 CLEAR / 701 TAN / 702 WHITE

PVC (Polyvinyl Chloride) Carton Sealing Tape
for Hand Held Dispensers

Permissible Variations, Standards and Tolerances:

Except in the particulars specified by buyer and expressly agreed to in writing by VIBAC® CANADA INC., all goods or material shall be produced in accordance with VIBAC®'s standard practices. All goods or material, including that produced to meet an exact specification, shall be subject to tolerances and variations consistent with usages of the trade and regular manufacturing practices concerning: dimension, weight, straightness, section, composition and mechanical properties; normal variations in surface, internal conditions and quality; deviations from tolerances and variations consistent with practical testing and inspection methods; and regular manufacturing practices concerning over and under shipments. All "In - Stock" orders are subject to a ten percent (10%) over ship / under ship quantity and all "Non - Stock / Non - Standard" orders are subject to a fifteen percent (15%) over run / under run quantity.

Warranty and Limited Remedy:

Unless stated otherwise, Vibac warrants that each product meets the applicable specifications at the time Vibac manufactures the product. VIBAC MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the Vibac product is fit for a particular purpose and suitable for user's application especially when used in combination with other products. If the Vibac product is defective within the warranty period, your exclusive remedy and Vibac's and seller's sole obligation will be, at Vibac's option, to replace the product or refund the purchase price. All of Vibac products are limited to a warranty period of six (6) months from date of purchase.

Limitation of Liability:

Except where prohibited by law, VIBAC® and seller will not be liable for any loss or damage arising from the VIBAC® product, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

VIBAC® reserves the right to make changes without notice or obligation on our products and in the information published about them. The suggestions and information presented herein are based on our research and experience, and believed to be reliable, but accuracy or completeness is not guaranteed. They are only for guidance and are not warranties or binding descriptions. The advice of seller's technical staff is available to the trade, but seller, not controlling or supervising the subsequent manufacture, fabrication, or installation of its products or their use after sale, does not warrant or guarantee such advice.

Since VIBAC® has no control over the conditions under which our product is transported, stored, handled, used or applied, each buyer and user must determine by its own preliminary tests or otherwise whether a product is suitable for its purpose. **THE WARRANTY DESCRIBED SHALL BE IN LIEU OF ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE. NO ONE IS AUTHORIZED BY VIBAC® TO MAKE ORAL WARRANTIES.**

To request additional product information or to arrange for sales assistance, please call, toll free, 1-800-557-0192 or email your request to sales@vibac.com



This product is manufactured by a certified C-TPAT member under a quality system registered to ISO 9001 : 2000 and ISO 14001 : 2004 standards