

# CHR<sup>®</sup> 2965-8R

## Glass-Silicone Pressure Sensitive Adhesive Tape

**CHR 2965** is a silicone rubber/glass cloth backing coated with a high-temperature silicone adhesive.

### Features/Benefits

**CHR 2965** tape is designed to withstand both the punishing abrasion of grit blasting and the extreme temperatures/pressures associated with the plasma spray process. **CHR 2965** has a high-temperature silicone adhesive, which allows the product to withstand temperatures up to 260°C during the coating process. **CHR 2965** tape has excellent strength and flexibility, which allows for easy wrapping of complex shapes.

### Availability

Factory stock for 2965 is in master rolls 33 m x 1219 mm (36 yd x 48 in). Rolls can be slit in widths ranging from 6.35 mm to 1219 mm (0.25 in to 48 in). **CHR 2965** is available with a yellow PVC liner.

### Applications

**CHR 2965** is used in the plasma spray process—a method of applying thin coatings of metal or high-temperature ceramics to a surface. The coating is sprayed at high pressure and at extreme temperatures. The tape is applied adjacent to areas of parts, which are to be plasma sprayed. **CHR 2965** tape protects these areas both from the grit blasting, which is used as a surface preparation, and from the actual plasma spray coating. The aerospace industry is the prime market for the use of plasma spray tapes, specifically, jet engine manufacturers, overhaul centers, major airline maintenance centers, Air Force Bases, and Naval Air Rework Facilities.



## CHR 2965-8R Properties

Performance tests are run using standard test procedures.

The values presented are typical values and should not be used for specification purposes.

Product Number	2965-8R
Backing Material	Glass-Silicone
Adhesive Type	Silicone
Total Thickness mm (mil)	0.267 (10.5)
Backing Thickness mm (mil)	0.178 (7.0)
Adhesive Thickness mm (mil)	0.089 (3.5)
Adhesion to Steel N/cm (oz/in)	5.0 (45)
Tensile Strength N/cm (lb/in)	175 (100)
Dielectric Strength (volts)	4,000
Elongation (% at break)	15
Operating Temperature °C (°F)	-73 to +260 (-100 to +500)
Colour	Blue



### Performance Plastics - Tape Solutions

North America | South America | Europe | Asia

For a full list of locations, please visit  
[tapesolutions.saint-gobain.com/contact-us](https://www.tapesolutions.saint-gobain.com/contact-us)

**IMPORTANT:** It is the user's responsibility to ensure the suitability and safety of Saint-Gobain Performance Plastics products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain Performance Plastics assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

**WARRANTY:** For a period of 6 months, Saint-Gobain Performance Plastics warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1134 | © Saint-Gobain March 2018 | **CHR** and **CHRTape** are trademarks of Saint-Gobain.