

CHR® M SERIES

2 Mil Polyester, Acrylic Adhesive Tape

CHR M-Series (2 Mil PET/Acrylic Adhesive) is manufactured from polyester film with acrylic pressure-sensitive adhesive.

Features/Benefits


M99 has a printable surface and compatible adhesive and release coating for excellent printability whether pre-printed on roll or a finished component. M99 offers excellent flagging resistance and has an excellent solvent and oil resistance. The tape is clean cutting with no adhesive separation. The adhesive can be thermoset to increase adhesion and solvent resistance. M99 also offers good conformability and is capable of meeting MIL-I-15126F-MF 3.5 specifications.

Availability

Factory stock for M99 is in master log form 66 m x 965 mm (72 yd x 38 in) wide. Rolls can be slit from 12.7 mm to 965 mm (0.5 in to 38 in) wide. M99 is available with or without a liner.

Applications

The 2.0 mil polyester film of **CHR** M99 was designed to provide an economical method to hold, insulate and protect various materials.



CHR M Series 2 Mil Polyester Acrylic Tape Properties

Performance tests are run using standard test procedures.

The values presented are typical values and should not be used for specification purposes.

| Product Number | M99 |
|--------------------------------|---------------------------|
| Adhesive Type | Acrylic |
| Total Thickness mm (mil) | 0.089 (3.5) |
| Adhesive Thickness mm (mil) | 0.038 (1.5) |
| Adhesion to Steel N/cm (oz/in) | 4.4 (40) |
| Tensile Strength N/cm (lb/in) | 88 (50) |
| Elongation (% at break) | 120 |
| Dielectric Strength (volts) | 7,000 |
| Operating Temperature °C (°F) | -29 to +163 (-20 to +325) |
| Insulation Class (°C) | 130 |
| Colour | Yellow |



Performance Plastics - Tape Solutions

North America | South America | Europe | Asia

For a full list of locations, please visit
tapesolutions.saint-gobain.com/contact-us

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain Performance Plastics products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain Performance Plastics assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: For a period of 6 months, Saint-Gobain Performance Plastics warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1104 | © Saint-Gobain January 2018 | **CHR** and **CHRTape** are trademarks of Saint-Gobain.