

## RG3

### 131# PET UTILITY FILAMENT TAPE

#### DESCRIPTION

A fiberglass reinforced, polyester backed, pressure-sensitive strapping tape with a natural rubber/resin adhesive. Medium strength and good adhesion.

#### PRODUCT APPLICATIONS

Designed for the majority of packaging, palletizing and utilizing applications.



3647 Cortez Road West | Bradenton, FL 34210 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
[www.itape.com](http://www.itape.com) | [info@itape.com](mailto:info@itape.com)

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/11

## INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

#### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

<b>Backing</b>	57ga Polyester
<b>Adhesive</b>	Natural Rubber/Resin
<b>Reinforcement</b>	Fiberglass
<b>Adhesion to Steel</b> (oz/in of width) (at 90 degrees peel angle)	38 (10.4 N/25mm)
<b>Tensile Strength</b> (lbs/in of width)	131 (574 N/25mm)
<b>Elongation</b> (at break)	3.3%
<b>Total Thickness</b> (mils)	5.1 (0.13 mm)
<b>Quick Stick</b> (oz/in of width) To Kraft To Steel	3 (0.8 N/25mm) 24 (6.6 N/25mm)
<b>Color</b>	Natural

