

Y2070

TRANSFER TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

Unsupported 4 mil solvent acrylic transfer tape. Provides excellent shear strength and adhesion and high initial tack allowing immediate/permanent bond to a variety of surfaces. Good resistance to U.V., heat, solvents and chemicals. Features an easy release 6 mil, 60# glassine paper liner (mustard).

Product is not repulpable.

PRODUCT APPLICATION

Laminating flexible materials such as foam substrates, textile labels, felt and fabrics (gasketing applications). Affixing nameplates, trophy, emblems, labels, decorative trims, wood veneer and plastics. Attachment of overlay materials and membrane switches (transportation and electronic markets).

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive	Solvent Acrylic
Adhesion to Steel (oz/in of width) PSTC-101	88 (24 N/25mm)
Total Thickness w/o Liner (mils) PSTC-133	4.0 (0.1mm)
Shear Adhesion to Steel (hours) 1" x 1" x 1 kg @ 77°F (25°C) PSTC-107	>48
Service Temperature	-40°F to +230°F (-40°C to +110°C)
Color	Clear



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 09/15

