

# ATG500

## 5 MIL REVERSE WOUND ACRYLIC TRANSFER TAPE

### DESCRIPTION

A 4.8mil (0.122mm) glass stabilized acrylic adhesive transfer tape with brown kraft paper liner reverse wound on a 1" plastic core. This product is specifically designed to be used in ATG dispensers. The ATG system automatically rewinds the tape's liner inside of the dispenser as the tape is applied (tape is dispensed without liner). Glass stabilization allow for cleaner unwinding. Excellent adhesion to paper, most plastic films, metal foils, etc. Ultra-violet light has little or no effect on adhesive. Extra mass of adhesive ensures bonding to rough & textured surfaces.

### PRODUCT APPLICATION

Used for mounting nameplates, picture framing, product assembly, design and packaging of prototypes, sealing envelopes, paper web splicing, and general mounting and holding. Photo safe.



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

[www.itape.com](http://www.itape.com) | [info@itape.com](mailto:info@itape.com)

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 09/12

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

#### Adhesive

Glass Stabilized  
Modified Acrylic  
Adhesive

#### Peel Adhesion

73 oz/in (20 N/25mm)

#### Temperature Resistance

-22°F ~ 230°F  
(-30°C ~ 110°C)

#### Total Thickness without Liner (mils) +/-10%

4.8 mil (0.122 mm)

#### Color

Clear

#### Liner Color

Brown Kraft

