

PT5

MULTI-SURFACE PAINTER'S TAPE

DESCRIPTION

A crepe paper masking tape coated with a pressure-sensitive, rubber based adhesive for use on walls, trim, glass, metals and lacquered/varnished surfaces. Clean removal up to 24 hours

PRODUCT APPLICATION

Designed for paint masking and other all-purpose applications. Can also be used for light-weight packaging, bundling, splicing and tabbing.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 10/15

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Coarse Crepe
Adhesive	Synthetic Rubber/Resin
Adhesion to Steel (oz/in of width) PSTC-101	41 (11.2 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	25 (109 N/25mm)
Elongation (% at break) PSTC-131	10
Total Thickness (mils) PSTC-133	5.75 (0.146mm)
Quick Stick to Steel (oz/in of width) PSTC-5	17.8 (4.9 N/25mm)
Quick Stick to Kraft (oz/in of width) PSTC-5	3.8 (1.04 N/25mm)
Application Temp. Range	+50°F ~ +90°F (+10°C ~ +32°C)
Operating Temp. Range	+40°F ~ +150°F (+4°C ~ +66°C)
Color	Dark Blue

