

RG318

350# BOPP PREMIUM HOT MELT FILAMENT TAPE

DESCRIPTION

A high-strength fiberglass reinforced biaxially-oriented polypropylene (BOPP) film backing with an aggressive "solventless" pressure-sensitive adhesive. Exhibits high impact strength and adhesion.

PRODUCT APPLICATIONS

Provides excellent adhesion and "stiffness" for L-Clip closure applications. Also for bundling, strapping, and tabbing applications.

GOVERNMENT COMPLIANCE

Complies with the Federal Food, Drug and Cosmetic Act, CFR Title 21, Subpart B, Par. 175.105 (covers the use of pressure-sensitive adhesives and tapes for 'indirect contact' food packaging).



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/14

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing 1.1 Mil (28μ) BOPP Film

Adhesive Synthetic Rubber/Resin

Reinforcement Fiberglass

90° Adhesion to Steel 68 (18.6 N/25mm)
(oz/in of width)

Tensile Strength 350 (1532 N/25mm)
(lbs/in of width)

Elongation 4
(% at break)

Total Thickness 6.4 (0.16mm)
(mils)

Color Clear

Operating Temp Range -25°F to +140°F
(-32°C to +60°C)

