

## RG400

### 100# BOPP MEDIUM GRADE FILAMENT TAPE

#### DESCRIPTION

An economical fiberglass reinforced polypropylene film combined with an aggressive 'solventless' pressure-sensitive adhesive. Provides resistance to filament delamination and separation, excellent adhesion to corrugated cartons and outstanding holding power. Will hand break, no knives needed.

#### PRODUCT APPLICATIONS

Designed for the majority of packaging, palletizing and unitizing applications.



3647 Cortez Road West | Bradenton, FL 34210 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 07/10

## INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

#### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

<b>Backing</b>	1.1 Mil (28μ) Biaxial Oriented PE Film
<b>Adhesive</b>	Synthetic Rubber/Resin
<b>Adhesion to Steel</b> (oz/in of width) (at 90 degrees peel angle)	75 (20 N/25mm)
<b>Tensile Strength</b> (lbs/in of width)	100 (438 N/25mm)
<b>Elongation</b> (at break)	4%
<b>Total Thickness</b> (mils)	5.3 (.102mm)
<b>Quick Stick</b> (oz/in of width) To Kraft To Steel	8 (2.2 N/25mm) 45 (12.3 N/25mm)
<b>Shear to Kraft Paper</b> (hrs) (1" x 1" x 1000 grams)	Greater than 166
<b>Operating Temperature Range</b>	+20°F ~ +140°F (+6°C ~ +60°C)
<b>Color</b>	Clear

