

546

SPECIALTY COLORED IDENTIFICATION KRAFT FLATBACK TAPE

DESCRIPTION

A moisture resistant flatback, medium tensile strength, pressure-sensitive, packaging and identification tape. Product is not repulpable.

PRODUCT APPLICATIONS

Designed for packaging, bag locking, marking bins and shelves, decorative edging and color coding.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/16

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Kraft Flatback
Adhesive	Natural / Synthetic Rubber
Adhesion to Steel (oz/in of width) PSTC-101	60 (16.4 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	48 (210 N/25mm)
Elongation (% at break)	3
Total Thickness (mils) PSTC-133	7.3 (0.185mm)
Color	White, Yellow, Red, Green, Black

