

AC43

12 MIL MEDIUM GRADE DUCT TAPE

DESCRIPTION

Polyethylene coated cloth tape with an aggressive pressure sensitive natural rubber adhesive provides a wide range of temperature resistance. Designed to meet the needs of the general contractor.

PRODUCT APPLICATION

General Contractor, HVAC (Heating, Ventilation, and Air Conditioning), asbestos / fiberglass / lead abatement.

GOVERNMENT COMPLIANCE

Tested in accordance with UL-723, HUD and BOCA codes.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 03/11

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	PE Film
Adhesive	Natural Rubber/Resin
Reinforcement	PET Cloth
Tensile Strength (lbs/in of width) PSTC-131	26 (114 N/25mm)
Elongation (% at break)	18
Adhesion to Steel (oz/in of width) PSTC-101	50 (13.7 N/25mm)
Total Thickness (mils) PSTC-133	12 (0.305mm)
Application Temp. Range	+40°F to +90°F (+4°C to +32°C)
Operation Temp. Range	+32°F to +180°F (0°C to +82°C)
Color	Silver

