

## PTHMF

### PREMIUM MASKING FILM FEATURING PG21 MASKING TAPE

#### DESCRIPTION

Stain resistant, temperature resistant, paper masking tape combined with strong, corona treated HDPE film for industrial, marine and automotive painting. The solvent and moisture resistant film permits worry free wet sanding preparation and allows for easy cornering/masking of curved surfaces. Repositionable/heat resistant rubber based pressure-sensitive adhesive provides secure hold to and clean removal from most surfaces. Works with solvent and water borne paint systems.

#### PRODUCT APPLICATION

Industrial, marine and automotive painting, masking and protection from overspray, dust or debris. Pre-taped and pre-folded for easy use with or without a dispenser.



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE 04/18

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

#### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Tape Backing</b>	Fine Crepe Paper
<b>Tape Adhesive</b>	Rubber / Resin
<b>Tape Total Thickness</b> (mils)	7.3 (0.185mm)
<b>Adhesion to Steel</b> (oz/in of width)	28 (7.7 N/25mm)
<b>Tape Temperature Resistance</b>	325°F (163°C)
<b>UV Resistance</b>	Limited
<b>Weather Resistance</b>	Limited
<b>Color</b>	Natural
<b>Film Backing</b>	Virgin HDPE
<b>Film Total Thickness</b> (mils)	0.35 (9.0µ)
<b>Color</b>	Clear
<b>Film Temperature Resistance</b>	230°F (110°C)

