

Convoy Heavy Duty Natural

HEAVY DUTY PAPER TAPE

DESCRIPTION

Natural kraft carton sealing tape manufactured with standard water-activated adhesive.

PRODUCT APPLICATION

Recommended for lightweight or standard size cartons that will be shipped in unitized loads or full pallets.

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

CONSTRUCTION PER 3,000 SQUARE FEET (metric)

Paper: 85 lb (138 g/m²)
Natural Kraft Paper

Water-Activated Adhesive: Chemically Grafted
Starch Based Copolymer,
Designated as IPG 2001

PHYSICAL PROPERTIES:

Caliper 7.7 mils (0.20mm)
MD Tensile 71 lbs/in (311 N/25mm)
CD Tensile 28 lbs/in (123 N/25mm)

ADHESION (WATER AT RECOMMENDED 110°F/43°C)

Fipago:

2/0	20
2/1	40
5/0	46
15/0	84

McLaurin: 33



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 03/16

