

Heavy Duty Tuff Tape Natural

HEAVY DUTY PAPER TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

Natural kraft carton sealing tape manufactured with water-activated adhesive.

PRODUCT APPLICATION

Recommend for lightweight or standard size cartons that will be shipped in unitized loads or full pallets.

CONSTRUCTION PER 3,000 SQUARE FEET (metric)

Paper: 78 lb (127 g/m²)
Natural Kraft Paper

Water-Activated Adhesive: Waxy Maize Starch Based Adhesive,
Designated as #410

PHYSICAL PROPERTIES:

Caliper 8 mils (0.20mm)
MD Tensile 65 lbs/in (285 N/25mm)
CD Tensile 28 lbs/in (123 N/25mm)

ADHESION (WATER AT RECOMMENDED 110°F/43°C):

Fipago:

| | |
|------|----|
| 2/0 | 20 |
| 2/1 | 40 |
| 5/0 | 46 |
| 15/0 | 84 |

McLaurin: 33



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 03/16

