

# M2460

## DOUBLE-COATED FLATBACK PAPER TAPE

### DESCRIPTION

Flat-back paper coated on both sides with a semi-removable pressure-sensitive thermosetting rubber adhesive that provides shear strength, good adhesion and initial tack allowing immediate bond to a variety of surfaces. Dimensional stability/suitable for die-cutting requirements.

Features an easy release 3.5 mil glassine paper liner 60# (white).

**Product is not repulpable.**

### PRODUCT APPLICATION

Industrial grade mounting and fastening applications. For temporary hold down of parts while machining. For fastening of extruded plastic and rubber. For golf grips and bike grips. Protects pallets and holds garments to pallets during screen printing process. Temporary fixing of nameplates, signs and emblems for clean, quick removal.



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/17

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Flatback Paper
<b>Adhesive</b>	Thermosetting Rubber
<b>Adhesion to Steel</b> (oz/in of width) PSTC-3	56.4 (15.4 N/25mm)
<b>Total Thickness w/o Liner</b> (mils) PSTC-133	7.0 (0.178mm)
<b>Shear Adhesion to Steel</b> (hours) 1" x 1" x 2 kg @ 77°F (25°C) PSTC-107	>24
<b>Service Temperature</b>	-4°F to +140°F (-20°C to +60°C)
<b>Color</b>	White

