

tesa Softprint® 52816 Secure

Plate mounting tape for photopolymer plates in flexographic printing

Double-coated foam tape

Foam Properties

- Low thickness tolerance
- Long lasting, constant recovery characteristics

Adhesive Properties

- Low tack surface characteristics
- Strong adhesion on both sides
- Solvent resistance

Additional Properties

- Structured PP liner
- Logo color indicates foam hardness

Main Application

Mounting of 1.14 mm (0.45") and 1.70 mm (0.067") thickness, PET backing, flexographic printing plates onto steel / alu / PU and glassine cylinders and sleeves.

Technical Data

▪ Backing material	PE foam with film lamination	▪ Type of liner	PP
▪ Total thickness	430 µm 16.9 mils	▪ Logo color	purple
▪ Thickness category	380 µm 15 mils	▪ Hardness	medium
▪ Type of adhesive	tackified acrylic		

For latest information on this product please visit <http://l.tesa.com/?ip=52816>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.