

tesa® 4137

Aluminized polyester splicing tape

tesa® 4137 is a single-sided product with an aluminized, polyester carrier based on an acrylic adhesive system. tesa® 4137 offers excellent heat resistance and easy unwinding.

tesa® 4137 features

- High reflection of both light and heat radiation
- High aging resistance
- High shear strength

Main Application

- Splicing in high temperature situations, including infrared radiation
- Splicing plastic coated wallpaper with embossed surfaces
- Splicing leaders for photo development
- Can be used as sensor tape for proximity detector switches and optical detection switches
- Repairing and fixing in screen printing process

Technical Data

▪ Backing material	PET film	▪ Adhesion to steel	6 N/cm
▪ Color	silver	▪ Elongation at break	54.8 oz/in
▪ Total thickness	50 µm	▪ Tensile strength	140 %
	2 mils		50 N/cm
▪ Type of adhesive	acrylic		28.6 lbs/in

For latest information on this product please visit <http://l.tesa.com/?ip=04137>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.