


PE Coated Moisture Barrier Tape



Backing:	PE Coated Cloth
Adhesive:	Black Blended Rubber
Temp. Resistance:	105 °C (continuous)
Colors:	Black
Standard Sizes:	48mm x 55m, 72mm x 55m

Applications

- Moisture barrier in automotive, RV, appliance, and marine manufacturing
- Spot taping
- Wire harness splice insulation

Features

- Composite Cloth Backing
- Rubber Adhesive

Benefits

- Easy tear and application
- Excellent conformability for wrapping
- Moisture resistant
- High adhesion
- Performs in high humidity environments
- Low VOC

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	10.5 mils	0.267 mm	ASTM D-1000
Adhesion to Steel	43 oz/in	4.70 N/cm	PSTC-1
Adhesion to Backing	32 oz/in	3.50 N/cm	PSTC-1
Tensile Strength	32 lb/in	56.04 N/cm	ASTM D-1000
Unwind Force	29 oz/in	3.17 N/cm	PSTC-8
Elongation	6%		ASTM D-1000
Moisture VTR	0.8 g/100in ² /24hrs		FLTMBUI-1
Water Penetration	0.3 oz	8.3 g	FLTMBUI-2
Temperature Rating	105 °C		
Shelf Life at 25°C	24 Months		

Recommended Storage Conditions: 60-80 °F at 40-60% RH
Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.