


POLYKEN® 626-20

Foilastic® Window & Door Flashing Tape



Backing: 2 mil Aluminum Foil - Printed

Adhesive: Butyl Rubber

Liner: White Kraft Paper

Colors: Aluminum

Specifications: AAMA-711, ASTM E2112
15 Year Limited Warranty

Standard Sizes: 4" x 100ft, 6" x 100ft, 9" x 100ft

Applications

- Window and door installations
- Corner board abutments
- Sidewall sheathing seams
- Deck-to-wall joints
- Sealing other detail areas against water and air penetration

Features

- 2 mil Aluminum Foil Backing
- Premium Butyl Rubber Adhesive
- Kraft Paper Release Liner

Benefits

- Conformable and durable
- Excellent air and moisture barrier properties
- Suitable for indefinite outdoor UV exposure
- Provides permanent weather-tight seal on most clean, dry building surfaces
- Excellent all-temperature performance
- Compatible with sealants and caulking
- Self-healing after puncture
- Easy to remove

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	20.0 mils	0.508 mm	ASTM D-1000
Adhesion to Steel	279 oz/in	30.52 N/cm	ASTM D903-93
Adhesion to Plywood	96 oz/in	10.50 N/cm	ASTM D903-93
Adhesion to OSB	76 oz/in	8.31 N/cm	ASTM D903-93
Adhesion to PVC	200 oz/in	21.88 N/cm	ASTM D903-93
Adhesion to Housewrap	232 oz/in	25.38 N/cm	ASTM D903-93
Tensile Strength	18 lb/in	31.52 N/cm	ASTM D-1000
Installation Temperature	30 to 180 °F	-1 to 82 °C	
Operating Temperature	-30 to 200 °F	-34 to 93 °C	

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.