

Technical Data Sheet

3M™ Scotch® Filament Tape 898

Product Description

Scotch® Filament Tape 898 is a high-performance transparent packaging tape reinforced along its length with continuous glass-yarn filaments, which give the tape very high tensile strength. The transparent polypropylene backing provides excellent abrasion, moisture and scuff resistance. The adhesive is an aggressive packaging adhesive specifically formulated to provide balanced performance having both high adhesion and long term holding power.

Product Features

- Meets ASTM D5330, Type II (replaces PPP-T-97E and CID A-A-1686A).
- Abrasion and moisture resistant.
- Good handling.
- High tensile strength.
- Allows printing and illustrations to be seen through the tape.
- High shear and great initial adhesion.
- Excellent aging.
- Good protection of filaments and adhesive to provide longer package life.
- Assures maximum package performance for limited outdoor use.
- Saves time through ease of dispensing and handling when used with a 3M dispenser.
- Provides advertising and warning capability when printed.
- Low unit costs by using less tape on applications where high tensile strength is one of the main requirements.
- Good holding, with minimum amount of tape, under a wide range of application conditions.
- Holds instantly with minimum rubdown.
- Boxes remain securely closed through normal warehouse time cycles.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values	Additional Information
Backing	Biaxial Oriented Polypropylene(BOPP)	
Adhesive Type	Pressure sensitive synthetic rubber resin	
Backing Color	Clear	
Total Tape Thickness (mil)	6.6 mil	View 
Test Method: ASTM D3652		

Total Tape Thickness (mm)	0.17 mm	View 
---------------------------	---------	--

Test Method: ASTM D3652

Fiber Reinforcement	Glass Yarn
---------------------	------------

Typical Performance Characteristics

Property	Values	Additional Information
----------	--------	------------------------

Tensile Strength	665 N/cm	View 
------------------	----------	--

Test Method: ASTM D3759

Tensile Strength (N/100mm)	6650 N/100mm	View 
----------------------------	--------------	--

Test Method: ASTM D3759

180° Peel Adhesion	7.7 N/cm	View 
--------------------	----------	--

Test Method: ASTM D3330

Notes: 12 in/min (300 mm/min)

180° Peel Adhesion	70 oz/in	View 
--------------------	----------	--

Test Method: ASTM D3330

Notes: 12 in/min (300 mm/min)

180° Peel Adhesion	77 N/100mm	View 
--------------------	------------	--

Test Method: ASTM D3330

Substrate: Stainless Steel

Tensile Strength (lb/in)	380 lb/in	View 
--------------------------	-----------	--

Test Method: ASTM D3759

Elongation at Break (%)	5 %	View 
-------------------------	-----	--

Test Method: ASTM D3759

Storage and Shelf Life

Store behind present stock. Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended. Rotate your stock. To obtain best performance, use this product within 18 months from date of manufacture.

Bottom Matter

3M
Industrial Adhesives and Tapes Division
3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550

Trademarks

Scotch is a registered trademark of 3M.
3M, 3M-Matic are trademarks of 3M.

Handling/Application Information

Application Techniques

An extensive line of application equipment including hand-held manual dispensers and the automatic 3M-Matic™ L-Clip Applicator S867 are available. Application of Scotch® Filament Tape 898 is most easily accomplished at room temperature.

At colder temperatures, approaching 32°F (0°C), the adhesive becomes firm. Once applied, Scotch® Filament Tape 898 performs well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/p/d/b40067693/
Safety Data Sheet SDS	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=898

Family Group

Link Tags:

• 898

Products	Backing	Adhesive Type	Tensile Strength (N/100mm)
898	Biaxial Oriented Polypropylene(BOPP)	Pressure sensitive synthetic rubber resin	6650 N/100mm

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this

warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.