

# tesa® 53318

Performance Strength Fiberglass Reinforced Filament Tape

## PRODUCT INFORMATION

### Product Description

tesa® 53318 is a medium tensile strength fiberglass reinforced filament tape. It has an aggressive, high shear resistant, synthetic rubber resin adhesive. Characteristics include high tear resistance and low elongation. Available Colors: Transparent

### Main Application

- Strapping, bundling, and palletizing
- Medium grade L-clipping and reinforcing applications

### Technical Data

■ Backing material	glassfiber & BOPP	■ Adhesion to steel	7.1 N/cm
■ Type of adhesive	synthetic rubber		64.9 oz/in
■ Total thickness	101.6 µm	■ Elongation at break	4.5 %
	4 mils	■ Tensile strength	219 N/cm
			125.1 lbs/in

Page 1 of 1 / As of 05/20/10

### tesa tape, inc.

5825 Carnegie Boulevard  
Charlotte, NC 28209  
Phone: 704 554 0707  
Toll Free: 800 426 2181  
Fax: 800 852 8831  
customer@tesatape.com

### Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170  
German Centre P 6-3-3Col.  
Lomas de Santa Fe  
Mexico D.F. C.P. 01210  
Phone: +52 (55) 5292 6978  
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.