

# tesa® 4541

Conformable uncoated cloth tape

## PRODUCT INFORMATION

### Product Description

tesa® 4541 is a highly tear-resistant uncoated cloth tape. It is based on a 145 mesh rayon fabric backing and natural rubber adhesive. tesa® 4541 is a very flexible and conformable tape convenient for a wide range of applications.

Features:

- good adhesion even on rough and oily surfaces
- adapts to uneven surfaces without creasing
- easy to write on, ideal marking tape
- very high tensile strength
- smooth and conformable
- available in 5 colors: black, white, grey, red, brown

### Main Application

- Manual and machine driven closure of heavy cartons, buckets and tins
- Sealing of film containers, junction boxes and gap closures
- Bundling of bars, rods and cables
- Cable harnessing
- Securing of edges
- Reinforcing of book covers
- Fixing of plastic clips to cable tubes
- Reinforcing of hockey sticks
- Various applications in animal health care for bandaging large and small animals

### Technical Data

■ Backing material	uncoated cloth	■ Tensile strength	120 N/cm 68.5 lbs/in
■ Total thickness	270 µm 10.6 mils	■ Temperature resistance (30 min)	130 °C 266 °F
■ Type of adhesive	natural rubber	■ Mesh	145 count per square inch
■ Adhesion to steel	3.6 N/cm 32.9 oz/in	■ Surface finish	matt
■ Elongation at break	12 %		

### Properties

■ Easy to write on	yes	■ Abrasion resistance	+
--------------------	-----	-----------------------	---

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=04541>

Page 1 of 1 / As of 07/07/13

### tesa tape, inc.

5825 Carnegie Boulevard  
Charlotte, NC 28209  
Phone: 704 554 0707  
Toll Free: 800 426 2181  
Fax: 800 852 8831  
customer@tesatape.com

tesa SE  
A Beiersdorf Company

<http://www.tesatape.com>

### Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170  
German Centre P 6-3-3Col.  
Lomas de Santa Fe  
Mexico D.F. C.P. 01210  
Phone: +52 (55) 5292 6978  
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.