

TPP200

SPECIALTY CLEAN REMOVAL MOPP

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

DESCRIPTION

Economical MOPP tape designed for temporary holding and surface protection of appliances. The rubber adhesive offers excellent adhesion and stain / residue free removal from painted metals, stainless steel, ABS plastic and other common appliance surfaces.

PRODUCT APPLICATION

Can also be used for general strapping, light bundling, unitizing and palletizing.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	2 mil (50µ) MOPP
Adhesive	Natural Rubber / Resin
Tensile Strength (lbs/in width) ASTM D-3759	90 (394 N/25mm)
Elongation (% at break) ASTM D-3759	26
Adhesion to Steel (oz/in width) ASTM D-3330	30 (8.2 N/25mm)
Total Thickness (mils) ASTM D-3652	2.6 (0.066 mm)
Temperature Resistance	+200°F (+95°C)
Color	White



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 08/11

